

Product Specifications For 315 GC



Engine

Net Power - ISO 9249 73.3 kW

Engine Model Cat C3.6

Engine Power - ISO 14396 74.4 kW

Engine Power - ISO 14396 (DIN) 101 hp (metric)

Net Power - ISO 9249 (DIN) 100 hp (metric)

Bore 98 mm

Stroke 120 mm

Displacement 3.6 l

Biodiesel Capability Up to B20¹

Emissions Meets U.S. EPA Tier 4 Final, EU Stage V, and Japan 2014 emission standards

Note (1) Net power advertised is the power available at the flywheel when the engine is equipped with fan, air intake system, exhaust system and alternator with engine speed at 2,400 rpm. Advertised power is tested per the specified standard in effect at the time of manufacture.

Note (2)

¹Cat diesel engines are required to use ULSD (ultra-low sulfur diesel fuel with 15 ppm of sulfur or less) or ULSD blended with the following lower-carbon intensity fuels** up to: 20% biodiesel FAME (fatty acid methyl ester)* or 100% renewable diesel, HVO (hydrotreated vegetable oil) and GTL (gas-to-liquid) fuels. Refer to guidelines for successful application. Please consult your Cat dealer or “Caterpillar Machine Fluids Recommendations” (SEBU6250) for details. * Engines with no aftertreatment devices can use higher blends, up to 100% biodiesel (for use of blends higher than 20% biodiesel, consult your Cat dealer).** Tailpipe greenhouse gas emissions from lower-carbon intensity fuels are essentially the same as traditional fuels.

Weights

Operating Weight	15400 kg
------------------	----------

Working Ranges And Forces

Maximum Digging Depth	5990 mm
Boom	Reach 4.65 m (15'3")
Stick	Reach R3 m (9'10")
Bucket	GD 0.68 m ³ (0.89 yd ³)
Maximum Reach at Ground Level	8690 mm
Maximum Cutting Height	9690 mm
Maximum Loading Height	7220 mm
Minimum Loading Height	2080 mm
Maximum Depth Cut for 2440 mm (8 ft) Level Bottom	5810 mm
Maximum Vertical Wall Digging Depth	5180 mm
Minimum Working Equipment Radius	2240 mm
Bucket Digging Force - ISO	98.67 kN

Stick Digging Force - ISO

59.29 kN

Hydraulic System

Main System - Maximum Flow 247 L/min (65 gal/min)

Maximum Pressure - Equipment 35000 kPa

Maximum Pressure - Travel 35000 kPa

Maximum Pressure - Swing 26000 kPa

Swing Mechanism

Swing Speed 11.5 r/min

Maximum Swing Torque 35 kN·m

Service Refill Capacities

Fuel Tank Capacity 187 l

Cooling System 15 l

Engine Oil 8 l

Final Drive - Each 3 l

Hydraulic System - Including Tank 85 l

Hydraulic Tank 72 l

Dimensions

Boom Reach 4.65 m (15'3")

Stick Reach R3 m (9'10")

Bucket GD 0.68 m³ (0.89 yd³)

Shipping Height - Top of Cab	2810 mm
Handrail Height	2860 mm
Shipping Length	7440 mm
Shipping Length - with Blade	8010 mm
Tail Swing Radius	1570 mm
Counterweight Clearance	880 mm
Ground Clearance	440 mm
Track Length	3750 mm
Length to Center of Rollers	3040 mm
Track Gauge	1990 mm
Transport Width	2690 mm

Air Conditioning System

Air Conditioning The air conditioning system on this machine contains the fluorinated greenhouse gas refrigerant R134a (Global Warming Potential = 1430). The system contains 0.8 hg of refrigerant which has a CO2 equivalent of 1.144 metric tonnes.

315 GC Standard Equipment

NOTE

Standard and optional equipment may vary. Consult your Cat dealer for details.

BOOM AND STICKS

4.65 m (15'3") Reach boom

CAB

Rollover protective structure (ROPS)

Comfort Cab: air suspension seat, 203 mm (8") touch screen monitor

CAT TECHNOLOGIES

VisionLink®
Remote Flash

ELECTRICAL SYSTEM

Maintenance free battery
LED chassis light, left-side boom lights, cab lights
Programmable time-delay LED working lights
Centralized electrical disconnect switch

ENGINE

Cat C3.6 single turbo diesel engine
Auto engine speed control
Automatic engine shutdown
52°C (125°F) high-ambient cooling capacity without de-rate
-25°C (-13°F) cold start capability
Electric fuel priming pump
Variable speed fan
Single fuel filtration system
Double element air filter with integrated precleaner
Biodiesel capability up to B20

HYDRAULIC SYSTEM

Boom and stick regeneration circuit
Auto two speed travel
Electric main control valve
Boom and stick drift reduction valve
Single type electronic pump

SAFETY AND SECURITY

Rear and right-side-view cameras
Ground-level engine shutoff switch
Service platform with anti-skid plate and countersunk bolts
Signaling/warning horn
Auto Hammer Stop

SERVICE AND MAINTENANCE

Grouped engine oil and fuel filters
Ground-level engine oil dipstick
Sampling ports for Scheduled Oil Sampling (S·O·S)
Integrated vehicle health management system
Lockable disconnect switch

UNDERCARRIAGE AND STRUCTURES

Grease lubricated track link
Tie down points on base frame
3830 kg (8,440 lb) counterweight

315 GC Optional Equipment

NOTE

Standard and optional equipment may vary. Consult your Cat dealer for details.

BOOM AND STICKS

2.8 m (9'2") Reach stick
2.8 m (9'2") Thumb Ready Reach stick
3.0 m (9'10") Reach stick

CAB

Operator Protective Guards (OPG)

HYDRAULIC SYSTEM

Medium-pressure line
High-pressure line
Quick coupler line

SAFETY AND SECURITY

Swing alarm
Inspection lighting

CAT TECHNOLOGIES

VisionLink Productivity

UNDERCARRIAGE AND STRUCTURES

500 mm (20 in) triple grouser shoes
500 mm (20 in) triple grouser shoes with rubber pad
500 mm (20") rubber track shoes
600 mm (24") triple grouser shoes
600 mm (24") rubber track shoes
700 mm (28") triple grouser shoes
2,500 mm (8'2") blade
2,600 mm (8'6") blade
2,700 mm (8'10") blade